



2"/3" flanges

P/N	Flange O.D.		Blade OD 2.188"		Blade OD 2.250"		Blade OD 3.000"	
	[inch]	[mm]	[inch]	[mm]	[inch]	[mm]	[inch]	[mm]
2" Flanges			Exposure					
4B785-4175-000	1.750	44.45	0.219	5.56	0.250	6.35	0.625	15.88
4B785-4176-000	1.760	44.70	0.214	5.44	0.245	6.22	0.620	15.75
4B785-4177-000	1.770	44.96	0.209	5.31	0.240	6.10	0.615	15.62
4B785-4178-000	1.780	45.21	0.204	5.18	0.235	5.97	0.610	15.49
4B785-4179-000	1.790	45.47	0.199	5.05	0.230	5.84	0.605	15.37
4B785-4180-000	1.800	45.72	0.194	4.93	0.225	5.72	0.600	15.24
4B785-4181-000	1.810	45.97	0.189	4.80	0.220	5.59	0.595	15.11
4B785-4182-000	1.820	46.23	0.184	4.67	0.215	5.46	0.590	14.99
4B785-4183-000	1.830	46.48	0.179	4.55	0.210	5.33	0.585	14.86
4B785-4184-000	1.840	46.74	0.174	4.42	0.205	5.21	0.580	14.73
4A785-4185-000-BBD	1.850	46.99	0.169	4.29	0.200	5.08	0.575	14.61
4A785-4186-000-BBD	1.860	47.24	0.164	4.17	0.195	4.95	0.570	14.48
4A785-4187-000-BBD	1.870	47.50	0.159	4.04	0.190	4.83	0.565	14.35
4A785-4188-000-BBD	1.880	47.75	0.154	3.91	0.185	4.70	0.560	14.22
4A785-4189-000-BBD	1.890	48.01	0.149	3.78	0.180	4.57	0.555	14.10
4A785-4190-000-BBD	1.900	48.26	0.144	3.66	0.175	4.45	0.550	13.97
4A785-4191-000-BBD	1.910	48.51	0.139	3.53	0.170	4.32	0.545	13.84
4A785-4192-000-BBD	1.920	48.77	0.134	3.40	0.165	4.19	0.540	13.72
4A785-4193-000-BBD	1.930	49.02	0.129	3.28	0.160	4.06	0.535	13.59
4A785-4194-000-BBD	1.940	49.28	0.124	3.15	0.155	3.94	0.530	13.46
4A785-4195-000-BBD	1.950	49.53	0.119	3.02	0.150	3.81	0.525	13.34
4A785-4196-000-BBD	1.960	49.78	0.114	2.90	0.145	3.68	0.520	13.21
4A785-4197-000-BBD	1.970	50.04	0.109	2.77	0.140	3.56	0.515	13.08
4A785-4198-000-BBD	1.980	50.29	0.104	2.64	0.135	3.43	0.510	12.95
4A785-4199-000-BBD	1.990	50.55	0.099	2.51	0.130	3.30	0.505	12.83
4A785-4200-000-BBD	2.000	50.80	0.094	2.39	0.125	3.18	0.500	12.70
4A785-4201-000-BBD	2.010	51.05	0.089	2.26	0.120	3.05	0.495	12.57
4A785-4202-000-BBD	2.020	51.31	0.084	2.13	0.115	2.92	0.490	12.45
4A785-4203-000-BBD	2.030	51.56	0.079	2.01	0.110	2.79	0.485	12.32
4A785-4204-000-BBD	2.040	51.82	0.074	1.88	0.105	2.67	0.480	12.19
4A785-4205-000-BBD	2.050	52.07	0.069	1.75	0.100	2.54	0.475	12.07
4A785-4206-000-BBD	2.060	52.32	0.064	1.63	0.095	2.41	0.470	11.94
4A785-4207-000-BBD	2.070	52.58	0.059	1.50	0.090	2.29	0.465	11.81
4A785-4208-000-BBD	2.080	52.83	0.054	1.37	0.085	2.16	0.460	11.68
4A785-4209-000-BBD	2.090	53.09	0.049	1.24	0.080	2.03	0.455	11.56
4A785-4210-000-BBD	2.100	53.34	0.044	1.12	0.075	1.91	0.450	11.43

4A785-4211-000-BBD	2.110	53.59	0.039	0.99	0.070	1.78	0.445	11.30
4A785-4212-000-BBD	2.120	53.85	0.034	0.86	0.065	1.65	0.440	11.18
4A785-4213-000-BBD	2.130	54.10	0.029	0.74	0.060	1.52	0.435	11.05
4A785-4214-000-BBD	2.140	54.36	0.024	0.61	0.055	1.40	0.430	10.92
4A785-4215-000-BBD	2.150	54.61	0.019	0.48	0.050	1.27	0.425	10.80
4A785-4216-000-BBD	2.160	54.86	0.014	0.36	0.045	1.14	0.420	10.67
4A785-4217-000-BBD	2.170	55.12	0.009	0.23	0.040	1.02	0.415	10.54
4A785-4218-000-BBD	2.180	55.37			0.035	0.89	0.410	10.41
4A785-4219-000-BBD	2.190	55.63			0.030	0.76	0.405	10.29
4A785-4220-000-BBD	2.200	55.88			0.025	0.64	0.400	10.16
4A785-4221-000-BBD	2.210	56.13			0.020	0.51	0.395	10.03
4A785-4222-000-BBD	2.220	56.39			0.015	0.38	0.390	9.91
4A785-4223-000-BBD	2.230	56.64			0.010	0.25	0.385	9.78
4A785-4224-000-BBD	2.240	56.90					0.380	9.65
4A785-4225-000-BBD	2.250	57.15					0.375	9.53
4A785-4226-000-BBD	2.260	57.40					0.370	9.40
4A785-4227-000-BBD	2.270	57.66					0.365	9.27
4A785-4228-000-BBD	2.280	57.91					0.360	9.14
4A785-4229-000-BBD	2.290	58.17					0.355	9.02
4A785-4230-000-BBD	2.300	58.42					0.350	8.89
4A785-4231-000-BBD	2.310	58.67					0.345	8.76
4A785-4232-000-BBD	2.320	58.93					0.340	8.64
4A785-4233-000-BBD	2.330	59.18					0.335	8.51
4A785-4234-000-BBD	2.340	59.44					0.330	8.38
4A785-4235-000-BBD	2.350	59.69					0.325	8.26
4A785-4236-000-BBD	2.360	59.94					0.320	8.13
4A785-4237-000-BBD	2.370	60.20					0.315	8.00
4A785-4238-000-BBD	2.380	60.45					0.310	7.87
4A785-4239-000-BBD	2.390	60.71					0.305	7.75
4A785-4240-000-BBD	2.400	60.96					0.300	7.62
4A785-4241-000-BBD	2.410	61.21					0.295	7.49
4A785-4242-000-BBD	2.420	61.47			-	-	0.290	7.37

P/N	Flange O.D.		Blade OD 2.188"		Blade OD 2.250"		Blade OD 3.000"	
	[inch]	[mm]	[inch]	[mm]	[inch]	[mm]	[inch]	[mm]
3" Flanges			Exposure					
4C785-4243-000	2.430	61.72	-	-	-	-	0.285	7.24
4C785-4244-000	2.440	61.98	-	-	-	-	0.280	7.11
4C785-4245-000	2.450	62.23					0.275	6.99
4C785-4246-000	2.460	62.48					0.270	6.86
4C785-4247-000	2.470	62.74					0.265	6.73
4C785-4248-000	2.480	62.99					0.260	6.60
4C785-4249-000	2.490	63.25					0.255	6.48
4C785-4250-000	2.500	63.50					0.250	6.35
4C785-4251-000	2.510	63.75					0.245	6.22
4C785-4252-000	2.520	64.01					0.240	6.10
4C785-4253-000	2.530	64.26					0.235	5.97
4C785-4254-000	2.540	64.52					0.230	5.84

4C785-4255-000	2.550	64.77				0.225	5.72
4C785-4256-000	2.560	65.02				0.220	5.59
4C785-4257-000	2.570	65.28				0.215	5.46
4C785-4258-000	2.580	65.53				0.210	5.33
4C785-4259-000	2.590	65.79				0.205	5.21
4C785-4260-000	2.600	66.04				0.200	5.08
4C785-4261-000	2.610	66.29				0.195	4.95
4C785-4262-000	2.620	66.55				0.190	4.83
4C785-4263-000	2.630	66.80				0.185	4.70
4C785-4264-000	2.640	67.06				0.180	4.57
4C785-4265-000	2.650	67.31				0.175	4.45
4C785-4266-000	2.660	67.56				0.170	4.32
4C785-4267-000	2.670	67.82				0.165	4.19
4C785-4268-000	2.680	68.07				0.160	4.06
4C785-4269-000	2.690	68.33				0.155	3.94
4C785-4270-000	2.700	68.58				0.150	3.81
4C785-4271-000	2.710	68.83				0.145	3.68
4C785-4272-000	2.720	69.09				0.140	3.56
4C785-4273-000	2.730	69.34				0.135	3.43
4C785-4274-000	2.740	69.60				0.130	3.30
4C785-4275-000	2.750	69.85				0.125	3.18
4C785-4276-000	2.760	70.10				0.120	3.05
4C785-4277-000	2.770	70.36				0.115	2.92
4C785-4278-000	2.780	70.61				0.110	2.79
4C785-4279-000	2.790	70.87				0.105	2.67
4C785-4280-000	2.800	71.12				0.100	2.54
4C785-4281-000	2.810	71.37				0.095	2.41
4C785-4282-000	2.820	71.63				0.090	2.29
4C785-4283-000	2.830	71.88				0.085	2.16
4C785-4284-000	2.840	72.14				0.080	2.03
4C785-4285-000	2.850	72.39				0.075	1.91
4C785-4286-000	2.860	72.64				0.070	1.78
4C785-4287-000	2.870	72.90				0.065	1.65
4C785-4288-000	2.880	73.15				0.060	1.52
4C785-4289-000	2.890	73.41				0.055	1.40
4C785-4290-000	2.900	73.66				0.050	1.27
4C785-4291-000	2.910	73.91				0.045	1.14
4C785-4292-000	2.920	74.17				0.040	1.02
4C785-4293-000	2.930	74.42				0.035	0.89
4C785-4294-000	2.940	74.68				0.030	0.76
4C785-4295-000	2.950	74.93				0.025	0.64
4C785-4296-000	2.960	75.18				0.020	0.51
4C785-4297-000	2.970	75.44				0.015	0.38
4C785-4298-000	2.980	75.69				0.010	0.25
4C785-4299-000	2.990	75.95	-	-	-	0.005	0.13